



AQUATHERMICA PRO WITH A HEAT EXCHANGER

## AQUATHERMICA PRO 260 S



SAP код	306267
Capacity	251 L
Height	1911 mm
Energy class	A+
Maximum operational temperature	75 °C
Maximum working pressure	8 bar
Diameter	630 mm
Heating time	9:37 h:min



Declared load profile	XL
Electric heating element power	1.5 kW
HP maximum absorption	$0.47 + 1.5 \text{ (e-heater)} = 1.970 \text{ kW}$
Min. ÷ max temperature heat pump air intake (90% R.H.)	$-7 \div 43 \text{ }^{\circ}\text{C}$
Frequency	50 Hz
Annual electricity consumption in kWh under average climate conditions	1160 kWh
Power supply	1/N/220-240 V
Compressor	Rotary
Min. ÷ max temperature installation site	$-4 \div 40 \text{ }^{\circ}\text{C}$
Compressor protection	Thermal circuit breaker with automatic reset
Maximum current in HP	$2.5 + 6.5 \text{ (e-heater)} = 9 \text{ A}$
Required overload protections	16A T fuse/ 16 A automatic switch characteristic C (to be expected during installation on power supply systems)
Fan	Centrifugal
HP Maximum settable temperature	$65 \text{ }^{\circ}\text{C}$
Internal protection	Single safety thermostat with manual reset on a resistive element
Nominal air capacity	$360 \text{ m}^3/\text{h}$
Motor protection	Internal thermal circuit breaker with automatic reset
Condenser	Wrapped externally not in contact with water
Transport weight	127.3 kg
Automatic anti-Legionella disinfection cycle	YES
Minimum height of the premise	2000 mm



Cathodic protection	Mg anode Ø 33 x 400 mm
Defrosting	Active with 4-way valve
CoP (DHW)	3.8
Degree of Protection	IPX4
Refrigerant	R290
Refrigerant charge	150 g



**Inspired by nature. Powered by technology**

**AquaThermica Pro** with a heat exchanger is a floor-standing air-to-water heat pump for domestic hot water, operating on eco-friendly propane (R290 refrigerant), and compatible with external energy sources such as boilers or solar systems

- Floor-standing "air-water" heat pump for domestic hot water production.
- Greater energy efficiency and performance are guaranteed by environmentally friendly refrigerant R 290 / propane/
- Electric heating element for faster heating and reaching a high temperature of 75°C.
- Automatic "Antilegionella" function and self-diagnosis system
- Floor standing models
- Energy class A+
- Reduced CO2 emissions
- Water tank capacity from 200 to 260 L
- **Up to 75%** reduced electricity consumption
- **Lateral 45° air ducts** for installation in rooms as low as 2 meters
- **Quiet operation:** just 34 dB(A) at 1 meter
- **DRY CHECK** Check the magnesium anode without draining the water.
- **Electronic Expansion Valve (EEV)** for precision refrigerant control
- **Microchannel condenser** and dual temperature sensors for performance and efficiency
- Up to 65°C DHW temperature with operation of only the heat pump unit
- Connection to solar and photovoltaic panels, compatible also with external energy sources such as boilers or solar systems
- User friendly electronic panel

**Inspired by nature. Powered by technology**



Using the natural R290 (propane) refrigerant, AquaThermica Pro achieves ultra-low Global Warming Potential (GWP) and zero Ozone Depletion Potential (ODP). It can heat water up to 65°C using only the heat pump, offering up to 75% energy savings versus conventional electric water heaters. Its high Coefficient of Performance (COP)—up to 3.8—makes it one of the most efficient systems in its class.

**Key Features:**

- Heat exchanger for system compatibility
- Lateral 45° air ducts for installation in rooms as low as 2 meters
- Quiet operation: just 34 dB(A) at 1 meter
- Electronic Expansion Valve (EEV) for precision refrigerant control
- Microchannel condenser and dual temperature sensors for performance and efficiency
- The highest energy efficiency class A+ in its category
- Operates within a wide temperature range of the incoming air starting from -7° C to 43 °C.
- Heats up water to 65° C with the heat pump only.
- Electric heating element for faster heating up and reaching of higher temperature of 75 °C
- Can be connected to other renewable energy sources like PV panels, solar systems or boilers.
- Programmable with a user-friendly control panel
- Smart operation modes: Boost, Eco, Intelligent, Vacation, High-Demand
- Anti-legionella function, Dry Check MG anode, and modular service design

***Compact, quiet, and eco-friendly, AquaThermica Pro is the ideal solution for modern homes looking to combine comfort, sustainability, and long-term savings.***